

STRONG

Digital HD Satellite Receiver

SRT 7600



Picture similar

Enjoy FTA, Xtra TV & Viasat TV satellite channels in best quality

SRT 7600 is the best choice for reception of the complete FTA, Xtra TV or Viasat TV range of satellite channels. This advanced HDTV receiver with bright pictures and clear sound combines excellent features and convenience. A USB port is located on the front panel for recording onto an external USB storage device and playback. Channels can be stored individually in 4 favourite lists. SRT 7600 also includes an Electronic Programme Guide, more than 4000 channels memory capacity and much more for a great viewing experience!

- HDTV receiver for FTA, Xtra TV or Viasat TV bouquet of channels over satellite¹
- Cardless embedded Conditional Access System for watching programmes encrypted by Verimatrix
- USB port: Timeshift and recording of TV programmes, playback of files².
- More than 4000 channels memory capacity
- Channel numbering as given by the operator
- Extremely bright and clear picture and excellent sound quality
- Electronic TV Programme Guide (EPG) for on screen programme information of up to 7 days³
- Booking of events directly from EPG



USB recording



Programme guide



Favourite lists



Digital audio



Timers

DVB-S2

HDMI™


HEVC Advance™

verimatrix.
DRIVING TRUST

Digital HD Satellite Receiver **SRT 7600**

- Teletext, full multi-lingual DVB subtitles and audio track support⁽³⁾
- 4 favourite lists for TV and radio programmes
- 16 event timers with various modes (once, daily, weekly, etc.)
- Ethernet port: access to RSS feeds and weather forecasts
- Parental lock function for menu and rating control for channel⁽³⁾
- Multi-lingual support on screen menu (OSD)
- Aspect ratio adjustment 4:3, 16:9, Pan&Scan, Letterbox
- Software update via OTA
- Automatic channel list update
- Power on with last viewed channel
- **Video/audio outputs:** HDMI, 3 RCA (Video, Audio L/R)
- Selectable resolution 1080p, 1080i, 720p and 576p
- Supports MPEG-4 H.264, H.265
- **Connectors:** SAT IN, USB, HDMI, 3 RCA (Video, Audio L/R), RJ-45 Ethernet, 12 V power supply

1 Subject to your local reception conditions
 2 STRONG cannot guarantee the playback of files although extensions are listed, as it depends on codec, data bit rate and resolution used (all MPEG codec formats are supported).
 3 Availability depending on the broadcast



1. Satellite antenna
2. Internet
3. TV (HDMI)
4. TV video (RCA)
5. TV audio (RCA)
6. Power adapter

Tuner

Input connector: IEC60169-24, female, 75 Ohm nominal
 Input frequency range: 950 ~ 2150 MHz
 Input signal level: -65 to -25 dBm
 LNB power: 13/18 V, max load 500 mA, overload protected
 DiSEqC version: 1.0 and 1.1

Demodulation

Demodulation modes: QPSK, 8PSK
 Symbol rate: 2~45 Msymb/s
 Transport stream input rate: up to 135 Mbit/s
 FEC decoder: DVB-S2: QPSK: 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
 8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10

Video decoder

Profile: MPEG-4 H.264/AVC, H.265/HEVC
 Input bit rate: Up to 50 Mbit/s for H.264
 Aspect ratio: 4:3 and 16:9, Letterbox, Pan & Scan, Auto
 Frame rate: 25 Hz for PAL
 Video resolution: 576p, 720p, 1080i, 1080p

Audio decoder

Audio mode: Mono L/R, Stereo
 Frequency response: 20 Hz ~ 20 kHz, unevenness in the frequency range 20 Hz ~ 20 kHz: + / - 0.5 dB
 Sampling rate: 32, 44.1, 48 kHz

Conditional Access System

System: Verimatrix Advanced Security+/SMI
 BISS mode 1

System and Memory

Processor: Ali3527
 System Memory: 256 MB DDR3
 Flash memory: NAND FLASH 128MByte

Front panel

Buttons: Stand-by, CH+, CH-, VOL+, VOL-
 Indicators: Bi-colour LED indicator (red: standby mode; green: working mode)
 Bi-colour LED indicator (red: blinking red: record/ Timeshift;

Connectors

SAT IN
 USB 2.0, Type A connector (max. 5 V, 500 mA)
 HDMI
 RCA (Video, Audio L/R)
 Ethernet
 Power supply (12 V, 1.5 A)

General Data:

Power supply: AC 100 – 240 V, 50/60 Hz
 Input voltage: DC 12 V, 1.5 A
 Power consumption: max. 18 W., typ. 6 W
 Power consumption in standby: 6 W
 Operating temperature range: 0° C ~ +40° C
 Storage temperature: -10° C ~ +50° C
 Operating humidity range: 10 ~ 85% RH, non-condensing
 Dimensions (W x D x H) in mm: 170 x 110 x 41
 Weight in kg: 0.49

EAN SRT 7600: 9120072370274

SUPPORT

UA support_ua@strong.tv
 +380 (44) 238 61 50

Subject to alterations. In consequence of continuous research and development technical specifications, design and appearance of products may change. Verimatrix is a registered trademark of Verimatrix, Inc. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc in the United States and other countries. All other product names are trademarks or registered trademarks of their respective owners. © STRONG 2018. All rights reserved.