# coocaa

## DIGITAL HD CABLE RECEIVER

**HDC2530** 





















USB Playback Programme guide Favorite lists Parental control

Te

Eco stand

#### Enjoy Digital Cable TV in HD with HDC2530 and its HDMI cable already included!

Among many cable operators already providing digital television via the cable network, the HDC2530 strikes the perfect balance for those seeking an affordable and easy-to-use cable receiver. Enjoy crystal-clear images and immersive audio directly in your living room, enhancing your viewing experience.

Equipped with a convenient USB port located on the front panel and, notably, an included HDMI cable right out of the box, the HDC2530 allows for effortless playback of media files and software updates. Stay informed about upcoming events with the Electronic Programme Guide (EPG), while the 32 favourite lists enable personalized sorting of TV and radio programs for seamless browsing.

- HDTV receiver for digital TV via cable
- 1 HDMI Cable included.
- USB port: playback, software updates
- Easy installation & user-friendly menu
- Electronic TV Programme Guide (EPG)
- Parental lock function for menu

- Excellent audio and video quality
- 32 favourite lists for TV and radio
- User-friendly remote control
- Multi-lingual support on screen menu (OSD)
- Teletext and multilingual audio tracks

# coocaa

### DIGITAL HD CABLE RECEIVER

#### **HDC2530**


- For all Free-to-Air digital SD and HD channels in all cable networks (1)
- 1 HDMI Cable included.
- Quick and easy installation & user-friendly menu
- Easy sorting of channels
- Supports Dolby® Digital Plus<sup>(2)</sup>
- Parental lock function for menu
- USB port for playback of files<sup>(3)</sup>, back-up of channel list and receiver software updates via USB storage device
- User-friendly remote control
- Electronic TV Programme Guide (EPG) for on screen programme information of present/following event information up to 7 days<sup>(4)</sup>
- Excellent audio and video quality
- Multi-lingual support on screen menu (OSD)
- Teletext, full multi-lingual DVB subtitling and audio track support(4)
- 32 favourite lists for TV and radio programmes
- 8 event timers with 4 modes (once, daily, weekly)

- 800 channels memory capacity
- High definition on screen display (OSD)
- Booking of events directly from the EPG
- Automatic and manual channel scan options
- Digital sound via coaxial output (S/PDIF) by connecting to digital amplifier
- USB power control for power saving in standby mode
- Fast channel zapping
- Power saving automatic standby function
- Channel handling options: lock, edit, move, sort, skip, delete and rename
- Power on with last viewed channel
- Connectors: Cable IN, cable OUT, S/PDIF, HDMI, TV SCART, USB
- Accessories: Remote control,

2x AAA batteries, Power adpater (12V/1A), HDMI cable

(1)Depending on local signal conditions
(2) Dolby, Dolby, Audio, and the double-D symbol are trademarks of Dolby Laboratories Licensing Corporation.
(3) CODCA: Cannot guarantee the playback of all files although extensions are listed, as it depends on codec used, data bit rate and resolution (all MPEC codec formats are supported).
(4) Availability depending on broadcaster





- 1. 4-digit 7-segment LED Display
- 2. Standby /On button
- 3. Program up/down button
- 4. USB port
- 1. Cable IN
- 2. Cable OUT (loop through)
- 3. S/PDIF (coaxial)
- 4. TV (HDMI)
- 5. TV (SCART)
- 6. Power adapter input (12 V/1 A)

Tuner Tuner

Rafael R850 75 Ohm Input Impedance:

Input Level: ≤ 40 dBuv (64 QAM) ≤ 44 dBuv (256 QAM)

Receiving Channel Range: 47 MHz ~ 862 MHz Modulation: 16, 64, 128, 256 QAM 3.6 M ~ 6.952 MS/s Symbol rate:

Video

Video resolution: 1920 x 1080 Decoding & Video Out: PAL & NTSC Aspect ratio:

Audio support: AC3+/PCM/Dolby® Digital Plus\*
MP1, MP2, HE-AAC, AAC-LC
\*Dolby, Dolby Digital, Dolby Digital Plus and the double-D symbol are registered trademarks of

System

DVB-C Transponder: Main Processor GX6701 64MB DDRAM FLASH size: 4 MB

Connectors Cable IN - IEC Female Cable OUT - IEC Male (Loop through) S/PDIF (coaxial)

TV SCART

USB 2.0 port: 5 V, 500 mA (max.) Power adapter input (12V/1A)

General data

100 - 240 V AC (SMPS), 50/60 Hz Supply voltage Power consumption 4W (typ.) 12W (max.)

Power consumption max 1W in standby:

Operating temperature: 0 ~ +40° C Storage temperature: Operating -10 ~ +70° C

humidity range:  $10 \sim 95\%$ , RH, Size (WxDxH) in mm:  $168 \times 95 \times 40$ 10 ~ 95%, RH, Non-condensing

Weight in kg: 0.223

Package Content 1x Receiver HDC2530 1x Remote Control 2x AAA batteries 1x HDMI cable

1x Installation instructions 1x Safety Instructions

> EAN: 9120072378409 PCB: 10



Subject to alterations. Technical alternations reserved. In consequence of continuous research and development technical specifications, design and appearance of products may change. The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. Manufactured under license from Dolby, Labonatories. Dolby, Dolby Audio and the double-D symbol are trademarks of Dolby Labonatories (Censing Corporation. All other product names are trademarks or registered trademarks of their respective owners.

COCOA.20.24. All rights reserved.

For additional information about the product, please access all documentation here: https://eu.strong-eu.com/downloads/