COOCQQ

DIGITAL HD SATELLITE RECEIVER HDS2610





Elevate your home entertainment experience with the Coocaa Digital HD Satellite Receiver HDS2610!

This receiver revolutionizes television viewing with advanced features and technology. Access 2000+ channels worldwide, enjoy personalized viewing with the built-in program guide. Browse through upcoming listings and plan your viewing schedule effortlessly, putting you in control of your entertainment.

Immerse yourself in the action with crystal-clear HD resolution and stunning Dolby sound. Take advantage of convenient features like subtitles, timers, and favourite lists to personalize your viewing experience. Whether you're catching up on your favourite series or setting reminders for important events, the Coocaa receiver has you covered. Easily connect your devices via HDMI port, ensuring a high-quality audio and video experience. Plus, with the included HDMI cable, setup is a breeze, allowing you to start enjoying your favourite content right away. Stay updated with software updates via USB for uninterrupted entertainment. Keep your receiver running smoothly and efficiently, ensuring you always have access to the best entertainment experience.

- HDTV receiver for digital Free-To-Air TV and radio programmes via satellite⁽¹⁾
- 1 HDMI Cable included
- Supports Dolby Audio[®] (2)
- USB port for software updates
- Supports SatCR for connecting up to 8 receivers to 1 SatCR LNB
- Display showing channel number in operating mode and time in standby
- 2000 channels/64 satellites memory capacity
- Exceptional picture quality and excellent sound (HD)
- USB port for playback of files⁽³⁾, back-up of channel list and receiver software updates via USB storage device
- Electronic Programme Guide (EPG) for on-screen information of present/next events for up to 7 days⁽⁴⁾
- Booking of events directly from EPG
- Up to 8 programmable timers

coocaa

COOCQQ

DIGITAL HD SATELLITE RECEIVER HDS2610

- Quick and easy installation & user-friendly menu
- Easy sorting of channels
- Power saving: switches to standby after a definable time
- Teletext and full multi-lingual DVB subtitling supported⁽⁴⁾
- Multiple audio track support⁽⁴⁾
- 8 favourite lists for TV and radio channels
- Parental control for locking selected channels with a password
- Multi-lingual On Screen Display (OSD)
- Easy to use channel handling options for finding, editing, moving, favouring and locking of channels
- Power on with the last viewed channel
- Video output via: HDMI, SCART (CVBS)

Digital audio output via S/PDIF coaxial for connection to a digital amplifier

HD

- Automatic, network and manual channel scan options
- Supports MPEG-2, MPEG-4 and H.264
- Supports DiSEqC 1.0, 1.1, 1.2, GOTO X, SatCR
- Connections: SAT IN, USB, HDMI, TV SCART, S/PDIF coaxial, Audio L/R, DC power
- Accessories: Remote control, 2x AAA batteries, power adapter

 (1)Depending on local signal conditions
(2) Dolby, Dolby Audio, and the double-D symbol are trademarks of Dolby Laboratories Licensing Corporation.

(3)COOCAA cannot guarantee the playback of all files although extensions are listed, as it depends on codec used, data bit rate and resolution (all MPEG codec formats are supported) (4) Availability depending on broadcaster

1. 4-digit 7-segment LED Display

2. Standby /On button

coocaa 8888 Dolby Audio ø Ø Ó наті CAUTION D/352 AA CEA ø

FEC

nouulator	
modulation:	QPSK, 8PSK Input symbol rate: DVB-S
	OPSK: 2 ~ 45 Ms/s DVB-S2 8PSK/OPS
	2~45 Ms/s
decoder:	Auto, 1/2, 2/3, 3/4, 5/6, 7/8 in DVB-S
	mode
	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 ir
	DVB-S2 mode 3/5, 2/3, 3/4, 5/6, 8/9,
	9/10 in 8PSK mode
	5/10 ITOI SI(TIOde

Max. 20 Mbit/s

Video Decoder Input rate: Aspect ratio: Video resolution:

16:9, 4:3 Pan&Scan, 4:3 Letterbox, Au 480i, 480p, 576i, 576p, 720, 1080i, 1080p, 50/60Hz

Audio decoding: MPEG-1/2 Layer 1 & 2 Audio mode: Stereo, L/R, Stereo Audio Support: E-AC3, Dolby Digital, Dolby Digital Plus* Sampling rate: 32, 44, 1, 48 kHz Dolby, Daby Digital, Dolby Digital Plus and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation. Audio Decoder

System & memory Main processor: Flash memory: Ali M3510G 8 MB System memory: 64 MB

	Tuner		
S	Type1 F Type, IEC169-24, Female		
SK:	Input frequency	050 0450141	
	range:	950 – 2150 MHz	
	RF impedance:	75 Ohm unbalanced	
	Signal level:	-65 to -25 dBm	
n	LNB power:	13/18 V DC (+/- 5%), max. 0.5 A,	
		overload protected	
	Switch versions:	DiSEqC 1.0, 1.1 LNB options: Universal,	
		SatCR (max. 8 users)	
	Motor drive options:	DisEqC 1.2, GotoX (DisEqC 1.3)	
uto.	Connectors		
	SAT IN		
	USB 2.0 port: Tvp A/500 mA (max.)		

HDMI 1 3 TV SCART (CVBS, Audio L/R) Audio L/R 3.5 mm /PDIF (coax.) Power adapter (12 V, 1.5 A)

Package content x Receiver HDS2610 1 x Remote Control 2 x AAA batteries 1x HDMI cable x Installation instructions 1 x Safety Instructions

1. SAT IN 2. HDMI

3. TV (SCART)

3. USB port

- 4. AUDIO R/L
- 6. Power adapter input (12 V/1.5 A)

General data Power supply: Input voltage: Power consumption: Power consumption	AC 100 – 240 V ~ 50/60 Hz DC 12 V, 1.5 A < 18 W
in standby:	max. 1 W
Operating temperature: Storage	0~+40°C
temperature:	-10 ~ +70℃
Operating humidity range: Size (W x D x H)	10 ~ 95% RH, non-condensing
in mm: Weight in kg:	168 x 95 x 36 incl. feet + connectors 0,260

EAN: 9120072378300 PCB: 5



Subject to alterations. Technical alternations reserved. In consequence of continuous research and development technical specifications, design and appearance of products may change. The terms HDM, HDM High-Definition Multimedia Interface, and the HDM Logo are trademarks or registered trademarks of HDM Licensing Administrator, Inc. Manufactured under license from DDB/suboratories. Dobby, DDB Avaidia and the double-D Symbol are trademarks or DDB Liboratories. All product names are trademarks or registered trademarks or of their respective owners © CDOCAA 2024, All rights reserved. For additional Information about the product, please access all documentation here: https://eustrong-eu.com/downloads/

00000

- - 5. S/PDIF (coaxial)