

## Universal Single LNB

### SRT L 702



### High quality signal strength

STRONG's state-of-the-art Universal Single LNB optimizes the signal strength and brings high performance to every home. It receives digital satellite signals in excellent SD, HD and the newest Ultra HD for high-quality TV pictures. With its compact housing and extra light weight weather and wind are no disturbing factors. Low noise figures and the particularly robust and high performing technology make this STRONG LNB a reliable and essential part of modern TV equipment.

- High performance technology
  - Built-in PLL\* technology guarantees high frequency stability
  - Excellent reception of digital Ultra HD, HD and SD signals
  - Ideal for system expandability
  - Extremely low noise figure (0,2 dB)
  - Robust and weather resistant
- \*Phase-locked loop

#### Technical specifications:

Input Frequency Range:  
Low band: 10.7 ~ 11.75 GHz  
High band: 11.7 ~ 12.75 GHz  
Output Frequency Range:  
Low band: 950 ~ 1950 MHz  
High band: 1100 ~ 2150 MHz  
LO Frequency:  
Low: 9.75 GHz  
High: 10.6 GHz  
LO Initial Accuracy:  
± 1.0 MHz (@25 °C);  
± 3 MHz (@-40 °C ~ +60 °C)  
Noise Figure: 0,2 dB (typ.)

Conversion Gain: 55 dB (typ.)  
DC Current Consumption:  
80 mA (max.)  
Polarization Switching Voltage:  
V: 11.5 ~ 14 V DC, H: 16 ~ 20 V DC  
Band Switching Pulse:  
Low: 0 Hz, High: 22 kHz  
Operation Temperature: -40 ~ +60 °C  
Output connector: 75 Ohm F type  
Dimensions (W x D x H):  
85 x 60 x 60 mm

EAN SRT L702: 8717185448931

