

Universal Repeater 300D

Boost your Wi-Fi network!



Do you have trouble getting solid Wi-Fi signals in some parts of your home?

STRONG's Universal Repeater 300D is the perfect solution to extend the coverage of your 802.11n modem or router in just minutes. At a maximum speed of 300 Mbit/s, the Universal Repeater 300D is a very compact solution designed for an extremely convenient placement.

STRONG's Universal Repeater 300D also includes 4 fast Ethernet ports to connect any wired devices to the network.

2x adjustable external antennas will boost a wide and reliable Wi-Fi coverage throughout your home.

The Universal Repeater 300D can also be configured as an outstanding 802.11n 300 Mbit/s Router.

Wi-Fi performance



- Supports 802.11n/b/g Wi-Fi standards
- Speed up to 300 Mbit/s
- 300 Mbit/s @ 2.4 GHz
- Universal Repeater and Router operational modes
- Works with any standard modem or router

Coverage & Reliability



- 2x adjustable external antennas for maximum coverage and reliability
- Connect & Secure (WPS) butt on for an easy setup

Security



- WPA/WPA2 for the highest level of Wi-Fi security
- Connect & Secure button (WPS) for an optimum network security

Connections



- 4x Ethernet LAN ports to connect any wired device
- 1x Ethernet WAN port to connect to your modem when configured as a Router



Universal Repeater 300D

Wi-Fi

Frequency 2.4 GHz

Standards IEEE 802.11 n /b/g, IEEE 802.3,

IEEE 802.3u

Signal Rate Up to 300 Mbit/s

Security WPA-Personal, WPA2-Personal,

WPA-Personal/WPA2-Personal

mixed mode

Antennas 2x 5dBi omnidirectional adjustable

antennas

Transmit Power Europe: <20 dBm (2.4 GHz)

Supported Channels

1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13

Features Repeater and Router operational

modes

Hardware

Interfaces 4x 10/100 Mbit/s LAN ports

(Auto MDI/MDIX)

1x 10/100 Mbit/s WAN port

(Auto MDI/MDIX)

Buttons Connect & Secure (WPS)/Reset

LEDs Power, Wi-Fi, WAN, LAN, Connect

& Secure (WPS)

Power External power supply, 5 V / 1 A DC

Standards IEEE 802.11n/g/b, IEEE 802.3,

IEEE 802.3u

Software

Configuration Wizards

Repeater, WISP, Router

Management Web User Interface, Time Settings,

Configuration Backup/Restore,

Firmware Upgrade

Internet Protocol IPv4

In Router Mode:

WAN Type Dynamic IP, Stati c IP, PPPoE

DHCP Server, DHCP Client List,

Address Reservation

Quality of Service Bandwidth Management for wired

and wireless devices

Port Forwarding Virtual Server, DMZ Dynamic DNS

DynDns

Security URL Filter, Access control for

wireless devices

Other specifications

Certification CE

Package contents Universal Repeater 300D

Ethernet Cable

Installation instructions

Warranty Card

System requirements

Windows 7, 8, 8.1, 10, Mac OS X,

Linux, Internet Browser

Environment Operating Temperature: 0 °C ~ +40 °C


Storage Temperature: $-40 \,^{\circ}\text{C} \sim +70 \,^{\circ}\text{C}$ Operating Humidity: $10\% \sim 90\%$ non-condensing Storage Humidity:

5% ~ 90% non-condensing

Dimensions (W \times D \times H)

225 x 136 x 25 mm

Weight: 0.16 kg



REPEATER300D: 9120072371714