

# DIGITAL HD SATELLITE RECEIVER SRT 7511































# Satellite TV in HD at its best!

Get the Austrian satellite programmes in HD (without smartcard) via ORF DIGITAL DIREKT with SRT 7511, additional to Free-To-Air TV and radio programmes! If you opt for a simpliTV "simpli more (SAT & Streaming)" subscription, you will also receive private German channels in the best HD quality. Set-up and installation of the receiver is quickly done. After choosing one of the four pre-installed channel lists, nothing stands in the way for watching TV in great quality. Many additional features are included to boost your TV experience: fast channel search, 10 favourite lists for individual sorting of TV and radio programmes, USB port for playback of files and software updates and much more. SRT 7511 provides satellite TV in HD at its best!

- Reception of Austrian satellite programmes in HD via ORF DIGITAL DIREKT and simpliTV<sup>1</sup>
- Reception of digital Free-To-Air TV- and radio programmes<sup>2</sup>
- 4 pre-sorted channel lists to choose for a quick & easy installation
- Dolby Digital Plus
- USB port: playback of files and update receiver software via USB storage device<sup>4</sup>
- Electronic TV Programme Guide (EPG) for on screen programme information and schedule for the following 7 days<sup>5</sup>
- Easy programming of timers through the EPG
- 8 favourite lists for TV and 2 for radio programmes
- Memory capacity of 5000 channels
- Various Timer modes for watching events
- Easy sorting of channels in favourite lists





# DIGITAL HD SATELLITE RECEIVER

### **SRT 7511**

- Find channels in the channel list easily through filter function
- Parental lock function
- Fast and high quality Teletext with selection of sub-pages via remote control4
- Subtitles and multiple audio tracks supported<sup>4</sup>
- Recall list for up to 30 channels
- Latest European satellites and transponder lists implemented
- Digital sound through coaxial output (S/PDIF)
- Auto DiSEgC function for a guick and easy installation of the most popular satellites<sup>6</sup>
- Disegc 1.0, 1.1, 1.2 and Goto-X

- Power saving: automatic standby after a definable time and configurable deep sleep setting
- Connectors: SAT IN, HDMI, TV SCART, S/PDIF coaxial, USB port (side), Ethernet, IR, power supply
- Accessories: Remote control, 2x AAA batteries, power adapter (12 V/1.5 A)
- Registration of the device at ORF DIGITAL with the enclosed registration form or on the Internet at digital.ORF.at is required.
- Subject to your local reception conditions
- Subject to your local reception conditions
  Dolby, Dolby Audio and the double-D symbol are trademarks of Dolby Laboratories.
  STRONG cannot guarantee the playback of files although extensions are listed, as it depends on codec used, data bit rate and resolution (all MPEG codec formats are supported).
  Availability depending on broadcast/Teletext via TV remote is only available via SCART
  The pre-configured satellites are: Astra 19.2E, Astra 23.5E, Astra 28.2E, HotBird 13.0E and Eutelsat 9.0E



- Satellite antenna 1.
- 2. Ethernet
- 3. Digital audio amplifier
- 4. TV (HDMI)
- 5. IR extender (not included in the packaging)
- 6. TV (SCART)
- 7. Power adapter

### Demodulator

Demodulator chipset: M1501 Demodulation: QPSK, 8PSK Input symbol rates:  $1 \sim 45$  Msps for DVB-S and DVB-S2 DVB-S/QPSK: 1/2, 2/3, 3/4, 5/6, 7/8 DVB-S2/QPSK: 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 DVB-S2/8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10

### Video Decoder

Video decoding: MPEG -4, AVC H.264 Aspect ratio: 4:3 and 16:9, Pan & Scan, Letterbox, Combined Frame rate: PAL and NTSC Video output: Scart: 576i, RGB, CVBS with CGMS-A HDMI: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p with HDCP

### Audio Decoder

Audio decoding: MPEG Layer 1 & 2, Dolby Downmix Audio mode: Mono L/R, Stereo Audio support: Dolby Digital Plus\* Transcoding for HDMI and S/PDIF: Dolby Digital Plus to Dolby Digital

Connector: Type1 F Type, IEC169-24, Female Chipset: RD5815M Input frequency range: 950 – 2150 MHz RF impedance: 75 Ohm unbalanced Signal level: -65 dBm ~ -25 dBm

LNB power: 13/18 V DC (+/- 1 V), 22 KHz (+/- 2 KHz), 400 mA, overload protected DiSEqC version: 1.0, 1.1, 1.2, GOTO X

### System & Memory

Main processor: Ali M3721 SD RAM: 256 MB (SIP /DDR3) Flash: 128 MB Nand

### Connectors

Ethernet HDMI TV SCART S/PDIF coaxial IR USB port 2.0, type A 5 V/500 mA (max.) DC main power (12 V/1.5 A)

## General Data

Power supply: 100 - 240 V AC, 50/60 Hz, 1.5 A Input voltage: 12 V DC, 1,5 A Power consumption: max. 18 W Power consumption in standby: max. 0.5 W Operating temperature: 0° C to +40° C Storage temperature: -10° C to +70° C Operating humidity range: 10 %-95 % RH, non-condensing Size (W x D x H) in mm: 175 x 55x 35 Weight in kg: 0.13

> EAN SRT 7511: 9120072371561 PCB: 10

07 Jun 2023 09:52

reserved

Dolby, Dolby Audio and the double-D symbol are trademarks of Dolby Laboratories

