

## Universal Repeater 300

Boost your Wi-Fi network!



### Do you have trouble getting solid Wi-Fi signals in some parts of your home?

STRONG's Universal Repeater 300 is the perfect solution to extend the coverage of your 802.11n modem or router in just minutes. At a maximum speed of 300 Mbit/s, the Universal Repeater 300 is a very compact wall plug solution designed for an extremely convenient placement.

The system of 2 adjustable external antennas combined with a smart LED System for an optimum positioning of the repeater will boost a wide and reliable Wi-Fi coverage throughout your home.

The Universal Repeater 300 can also be configured as an outstanding 802.11n Access Point or Router to immediately improve the Wi-Fi of your existing single band modem without exchanging it by a new one.

#### Wi-Fi Performance



- 802.11n Wi-Fi standard
- Speed up to 300 Mbit/s
- Supports 802.11n/b/g standards
- 300 Mbit/s @ 2.4 GHz
- Universal Repeater/ Access Point/Router operational modes
- Works with any standard modem or router

#### Coverage & Reliability



- 2x adjustable external antennas for maximum coverage and reliability
- Smart LED system for an optimum positioning of the repeater

#### Security



- WPA/WPA2 for the highest level of Wi-Fi security
- Connect & Secure button for an easy set up and a maximum network security
- Power on/off button

#### Connections



- 1x Ethernet LAN port to connect any computer, set-top-box, Smart TV, game console, ...
- 1x Ethernet WAN/ LAN port to connect to modem for Access Point/Router use
- Ethernet WAN/LAN port can be used as a second LAN port in Repeater mode

## Universal Repeater 300

### Wi-Fi

|                    |   |
|--------------------|---|
| Frequency          | 2.4 GHz   |
| Standards          | IEEE 802.11n/g/b  |
| Signal Rate        | Up to 300 Mbit/s  |
| Security           | WEP, WPA-Personal, WPA2-Personal, WPA-Personal/WPA2-Personal mixed mode |
| Antenna            | 2x 3 dBi omnidirectional, adjustable                                    |
| Transmit Power     | Europe: <20 dBm (2.4 GHz)   |
| Supported Channels | 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13                               |
| Features           | Enable/Disable, Client Isolation  |

### Hardware


|                |   |
|----------------|---|
| Ethernet Ports | 1x 10/100 Mbit/s LAN port (Auto MDI/MDIX)<br>1x 10/100 Mbit/s WAN/LAN port (Auto MDI/MDIX)    |
| Buttons        | Power On/Off, Operation mode selector (Repeater/Access Point/Router), Connect & Secure, Reset |
| LEDs           | Power/Connect & Secure, 3x Wi-Fi Smart LEDs, WAN, LAN   |
| Power          | Internal, 100-240 V, 50/60 Hz, 0.1 A  |
| Standards      | IEEE 802.11n/g/b, IEEE 802.3, IEEE 802.3u   |

### Software

|                       |   |
|-----------------------|---|
| Configuration Wizards | Repeater, Router, Access Point  |
| WAN Type              | Dynamic IP, Static IP, PPPoE  |
| DHCP                  | Auto, Server, Client  |
| Management            | Web User Interface, Time Settings, Configuration Backup/Restore, Firmware Upgrade |
| Internet Protocol     | IPv4  |

### Other specifications

|                        |  |
|------------------------|--|
| Certification          | CE   |
| Package contents       | Universal Repeater 300<br>Ethernet Cable<br>Installation instructions<br>Warranty Card   |
| System requirements    | Windows 7, 8, 8.1, 10, Mac OS X, Linux, Internet Browser   |
| Environment            | Operating temperature: 0° C ~ +40 °C<br>Storage temperature: -10° C ~ +70 °C<br>Operating humidity: 10%~90% non-condensing<br>Storage humidity: 10%~90% non-condensing |
| Dimensions (W x D x H) | 81 x 83 x 147 mm   |
| Weight:                | 0.13 kg  |



EAN REPEATER300V2: 9120072370748

PCB : 10 pcs